




1. MATERIAL:
 - Antenna Cover:TPEE
 - Antenna Base:PC+PBT
 - Color:Black
 - Operating Temperature: $-20^{\circ}\text{C} \sim +65^{\circ}\text{C}$
 - Storage Temperature: $-30^{\circ}\text{C} \sim +75^{\circ}\text{C}$
 - CABLE:MI-113
 - Connector:IPEX
 - Cable Length:(option)
2. ELECTRICAL
 - Frequency:2.4G/5.8G(DUALBAND)
 - Impedance:50Ω
 - VSWR ≤ 2.0
 - Gain:2.4GHz 1.5dBi, 5.8GHz 2.5dBi
 - Radiation:0 mni
 - Electronic Wave:1/4λ,Dipole
 - Polarization: Vertical
3. UNSPECIFIED TOLERANCE: .X ±0.50[0.011]

RoHS Compliant

		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347,Yang Guang St., Neihu , Taipei , Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: ø9 DUALBAND ANTENNA FOR IPEX		DWG NO: XANT-A003-B5002	
PART NO: XANT-A003-B5002		DRAWN: LEON	
		UNIT mm[inch]	SHEET 1 of 1
		REV 01	DATE: May.08,08