



1. MATERIAL:
 - Antenna Cover:PU
 - Antenna Base:PU UL 94V-0
 - Color:Black
 - Operating Temperature:-20° C~+65° C
 - Storage Temperature:-30° C~+75° C
 - SMA Connector(Optional):MALE PIN OR FEMALE PIN
2. ELECTRICAL
 - Frequency:2.4G/5.8G(DUALBAND)
 - Impedance:50Ω
 - VSWR ≤2.0
 - Gain:2.4GHz 1.5dBi, 5.8GHz 2.5dBi
 - Radiation:0 mni
 - Electronic Wave:1/4 λ ,Dipole
 - Polarization: Vertical
3. UNSPECIFIED TOLERANCE: .X ±0.50[0.011]

RoHS Compliant

X MULTIPLE		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: PART NAME Ø10 DUALBAND ANTENNA FOR SMA		DWG NO: XANT-A003-B5003	
PART NO: XANT-A003-B5003		DRAWN: LEON	
		CHKD: TARA	
		DATE: May.08,08	
UNIT mm[inch]	SHEET 1 of 1	REV 01	