



1. MATERIAL:
 Antenna Cover:PU
 Antenna Base:PC UL 94V-0
 Color:Black
 Operating Temperature:-20° C~+65° C
 Storage Temperature:-30° C~+75° C
 SMA Connector(OPTION):MALE PIN OR FEMALE PIN
2. ELECTRICAL
 Frequency:2.4G/5.8G(DUALBAND)
 Impedance:50Ω
 VSWR ≤2.0
 Gain:2.4GHz 1.5dBi, 5.8GHz 2.5dBi
 Radiation:0 mni
 Electronic Wave:1/4λ,Dipole
 Polarization: Vertical
3. UNSPECIFIED TOLERANCE: .X ±0.50[0.011]

RoHS Compliant

X MULTIPLE		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: φ13(132MM) DUALBAND ANTENNA FOR SMA		DWG NO: XANT-A003-B5005	
PART NO: XANT-A003-B5005		DRAWN: LEON	
		CHKD: TARA	
		DATE: May.08,08	
UNIT mm[inch]	SHEET 1 of 1	REV 01	