


Performance Specifications
Materials and Finish

Housing	Thermoplastic, UL 94V-0, Color Black
Contacts	Phosphor bronze plated with hard gold (optional) and Tin or gold flash in solder area
Shielding	Copper alloy plated with Nickel or Tin
Operating Temperature	0°C~70°C
Storage Temperature	-40°C~85°C

Mechanical Characteristics

Durability	500 Mating Cycles
Mating Force	5 Pounds Max.
Unmating Force	5 Pounds Max.

Electrical Characteristics

Current Rating	1.5 A Max.
Voltage Rating	150 VAC Max.
Insulation Resistance	500 MΩ Min.
Dielectric Withstanding Voltage	1000 VAC for 1 minute between adjacent contacts 1500 VAC for 1 minute between shield and contacts
Termination Resistance	40mΩ Max. Initial 50mΩ Max. Final

Features and Benefits

Vertical Mount LED modular jack for vertical mount to the PCB
LEDs located at top of jack for effective visibility
LEDs provided in a variety of color options
LEDs manufactured under license for U.S. Patent 4,978,317
Unshielded and shielded versions in popular size configurations
Reduce labor cost for PCB assembly
Meets or exceeds FCC part 68 rules and regulations with standard PCB footprints
Options : Internal LAN magnetics

Part Numbering:


