

SFP COPPER TRANSCEIVERS

Copper SFP Transceivers (10/100/1000Base-T)

FEATURES:

- Up to 1000BASE bi-direction data links
- 100m transmission over unshielded twisted pair (UTP) Category 5 Cable
- Hot-pluggable capability
- SGMII interface
- Support intelligent auto-negotiation 1000BASE-T operation in host systems
- SFP form with compact RJ-45 connector
- With spring latch for high density application
- Very low EMI and excellent ESD protection
- +3.3V single power supply
- Low power dissipation
- Operating case temperature: 0 to +70°C
- Detailed product information in EEPROM
- RoHS compliant



APPLICATIONS:

- LAN 1000Base-T
- Switch to Switch interface
- Switched backplane applications
- Router/Server interface



SFP COPPER TRANSCEIVERS

Copper SFP Transceivers (10/100/1000Base-T)

Transceiver PN# Chart:

Part Number	Package	Data Rate	Wavelength (nm)	Connector Type	Distance	Operating Temp(°C)	DDMI	Fiber Type
SL-SFP-1T	Copper SFP-T	10/100/1000M	N/A	RJ45	100M(UTP-5)	0-70	NO	N/A
SL-SFP-3T	Copper SFP-T	1000M	N/A	RJ45	100M(UTP-5)	0-70	NO	N/A
SL-SFP-2T	Copper SFP-T	10/100M	N/A	RJ45	100M(UTP-5)	0-70	NO	N/A

Please contact us at: info@xmultiple.com for more product information

