

## XRJM CONNECTOR SERIES

### FEATURES:

- RJ45 Connector, Tab-Up, Right Angle
- Available in 1, 2, 4, 6 and 8 Ports
- Through Hole Contacts
- Available with or without LEDs for Easy Viewing of Connection/Activity Status
- Compact Profile Saves PCB Space
- Available in Shield or Unshielded
- Minimum of 750 to 1000 Insertion Cycles



### GENERAL SPECIFICATION:

Product Type Features		Housing Related Features	
Tab Type	Tab Up	Material	PBT / Nylon
PCB Mount Angle	Side Entry (Right Angle)	Housing Flammability	UL 94V-0
Number of Ports	1, 2, 4, 6 and 8 Ports	Color	Optional
Number of Positions	8	Contact Features	
Number of Contacts	8	Material	Phos-Bronze
PCB Mount Style	Through Hole	Contact Area Plating	Hard Gold
LED	With or Without	Solder Area Plating	Tin / Gold Flash
Transformer	None	Magnetic Features	
Shielding Features		Transformer Speed	None
Material	Copper Alloy		
Plating	Nickel		
EMI Fingers	With or Without		
Number of PCB Ground Tabs	2 or 4		
Ground Pin Position (mm)	After Peg 3.43		

### ORDERING INFORMATION:

PART NO. X	PORT NO. X	Length X	Width X	Height X
XRJM-S-01-8-8-X	1 Port	15.70	16.45	13.40
XRJM-S-02-8-8-X	2 Port	15.70	32.20	13.40
XRJM-S-04-8-8-X	4 Port	15.70	63.70	13.40
XRJM-S-06-8-8-X	6 Port	15.70	95.20	13.40
XRJM-S-08-8-8-X	8 Port	15.70	126.70	13.40