



# RJ45 with LAN Magnetic Part Numbering System

**XXXX**

**XX**

**X**

**X**

**X**

**XX**

**X**

**X**

**X**

**Special Code**

**Product Series**

- XRJF:** Tab Down without LED
- XRJG:** Tab Down with LED
- XRJH:** Tab Up and Stacked with LED
- XRJB:** RJ45 over USB
- XRJV:** Vertical Mount

**Number of Ports**

- 01A:** 1 port for XRJF or XRJG w/Horizontal LED pin
- 01S:** XRJG 1 port w/Oblique LED pin
- 04A:** 4 port for XRJF or XRJG
- 01D:** XRJH 1 port , length = 25.4mm , straggered pins

- 04D:** XRJH 4 port , length = 25.4mm , straggered pins
- 01E:** XRJH 1 port , length = 21.6mm , straggered pins
- 01P:** XRJH 1 port , length = 25.53mm , straight pins
- 01R:** XRJH 1 port , length = 32.5mm , straight pins
- 24A:** 2\*4 port , Horizontal Pin , LED on top port only or w/o LED
- 26A:** 2\*6 port , Horizontal Pin , LED on top port only or w/o LED
- 28A:** 2\*8 port , Horizontal Pin , LED on top port only or w/o LED
- 21C:** 2\*1 port , Horizontal Pin , LED on top and bottom port
- 24C:** 2\*4 port , Horizontal Pin , LED on top and bottom port
- 26C:** 2\*6 port , Horizontal Pin , LED on top and bottom port
- 28C:** 2\*8 port , Horizontal Pin , LED on top and bottom port
- 21D:** 2\*1 port , Vertical Pin , LED on top port only or w/o LED
- 24D:** 2\*4 port , Vertical Pin , LED on top port only or w/o LED
- 26D:** 2\*6 port , Vertical Pin , LED on top port only or w/o LED
- 28D:** 2\*8 port , Vertical Pin , LED on top port only or w/o LED
- 24E:** 2\*4 port , Vertical Pin , LED on top and bottem port
- 26E:** 2\*6 port , Vertical Pin , LED on top and bottem port
- 28E:** 2\*8 port , Vertical Pin , LED on top and bottem port
- G7A:** RJ45 over Dual USB A type , G7 series , ground pegs Asymmetry
- G70:** RJ45 over Dual USB A type , G7 series
- K60:** RJ45 over Dual USB A type , K6 series
- B60:** RJ45 over USB B type , B6 series
- 01V:** XRJV , 1 port

**Mechanical Type**

**LED Color Option**


**Protocol Type**

- D.** 10/100, 4 core
- E.** 10/100, 5core
- H.** 10/100/1000, 8core
- L.** 10/100/1000, 12core

**Circuit Type**

**LED Polarity**

- 0.** w/o LED
- 1.** + - , + -
- 2.** + - , - +
- 3.** - + , - +
- 4.** BI-color , BI-color
- 5.** BI-color , + -
- 6.** BI-color , - +
- 7.** + - , BI-color
- 8.** - + , BI-color
- 9.** TRI-color , TRI-color



- 1.** Y=3.05, EMI finger on all side
- 2.** Y=3.05, Non- EMI finger
- 3.** Z=3.65, EMI finger on all side
- 4.** Z=3.65, Non- EMI finger
- 5.** Z=3.05, EMI finger on all side
- 6.** Z=3.05, Non- EMI finger
- 7.** EMI finger on all side
- 8.** Non- EMI finger
- 9.** 4 Port w/ 2 Tabs, Y=3.05, EMI finger on all side
- A.** 4 Port w/ 3 Tabs, Y=3.05, EMI finger on all side
- B.** 4 Port w/ 3 Tabs, Z=3.65, EMI finger on all side

**Shielded Type**