


	P1		P2
1	—	BLACK	— 1
2	—	BROWN	— 2
3	—	RED	— 3
4	—	ORANGE	— 4
5	—	YELLOW	— 5
6	—	GREEN	— 6
7	—	BLUE	— 7
8	—	PURPLE	— 8

NOTE:

1. 100% OPEN & SHORT TESTING
2. VOLTAGE: 300V DC
3. INSULATION RESISTANCE: 20M ohm
4. CONTACT RESISTANCE: 5 ohm

RoHS Compliant

<b>X MULTIPLE</b>		THE INFORMATION AGE	
XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475		XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: CABLE: RJ45 8P8C TO RJ45 8P8C PLUG		DWG NO: XCAB-6P08-1-6P08-001	
PART NO: XCAB-6P08-1-6P08-001		DRAWN: LEON	
		CHKD: TARA	
		DATE: Oct.07,08	
UNIT mm[inch]	SHEET 1 of 1	REV 01	

3	Ferrite core	STEWARD 28B0870-100 or EQUIVALENT	pcs	1
2	RJ45 connectors	8P8C PLUG, GOLD FLASH	pcs	2
1	Cable	UL 2464 26AWG 8C, OD:5.0mm COLOR:BEIGE	mm	58