



**NOTES:**

- ELECTRICAL CHARACTERISTICS:**  
 CONTACT CURRENT RATING: 3 AMPERES.  
 DIELECTRIC WITHSTANDING VOLTAGE: AC 1000/60SEC.R.M.S.  
 INSULATION RESISTANCE: 1000 MEGOHMS MINIMUM  
 CONTACT RESISTANCE: 25 MILLIOHMS MAXIMUM.  
 OPERATING TEMPERATURE: -55°C TO +105°C.
- MATERIALS:**  
 HOUSING: THERMOPLASTIC, UL 94V-0, COLOR: BLACK  
 CONTACT: COPPER ALLOY  
 SHELL: STEEL
- FINISHES:**  
 CONTACT: 30u" GOLD  
 SHELL: NICKEL
- UNSPECIFIED TOLERANCE:** XX ±0.25[0.010]  
 X ±0.30[0.012]

**XDSB-1-5-40-3-6-1-01-QUA**

1: D-SUB  
 5: RIGHT ANGLE DIP  
 PIN No. 25+15 PINS  
 SHELL PLATING 3: ALL NI  
 PIN PLATING 6: AU 30u"  
 HOUSING COLOR 1: BLACK  
 SERIAL NUMBER  
 CUSTOMER CODE

**RoHS Compliant**

<b>X MULTIPLE</b>		<small>THE INFORMATION AGE</small>	
<small>XMULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu, Taipei, Taiwan 11475</small>		<small>XMULTIPLE USA 1420 Los Angeles Ave., Suite G, Simi Valley, CA 93065</small>	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: D-SUB 0.318"(8.08) FOOTPRINT 25 FEMALE / 15 FEMALE DUAL PORT		DWG NO: XDSB-1-5-40-3-6-1-01-QUA	
PART NO: XDSB-1-5-40-3-6-1-01-QUA		DRAWN: RUNES	
		UNIT	SHEET
		mm[inch]	1 of 1
REV		DATE:	
01		Jul.24,08	
CHKD: TARA			