



| | | | | | | |
|----|---------------|----------|-----|-------------------------|---------------|------------|
| 7 | FERRULE | BRASS | 1 | GOLD | 3.2x2.3x8.7金 | C2700 |
| 6 | COVER | BRASS | 1 | GOLD | TC-2403J-9 | C3604 |
| 5 | BODY | BRASS | 1 | GOLD | TC-2403M-1 | C3604 |
| 4 | CENTER PIN | BeCu | 1 | GOLD (3u ^r) | TC-2403J-2-3u | C1730 |
| 3 | INSULATOR | TEFLON | 1 | - | TC-2403J-3 | ASTM D1710 |
| 2 | INNER CONTACT | BeCu | 1 | GOLD | TC-2403J-10 | C1730 |
| 8 | SHELL | BRASS | 1 | GOLD | TC-2403J-8 | C3604 |
| NO | DESCRIPTION | MATERIAL | QTY | FINISH | ITEM # | CODE # |

| DIMENSIONS(mm) | TOLERANCE | DRAWING | DESCRIPTION |
|----------------|-----------|-----------|-------------------------------------|
| 0-5mm | ±0.05 | DESIGNED | SSMB Plug R/A Crimp for RG178/RG196 |
| 5-10mm | ±0.1 | CHECKER | |
| 10-15mm | ±0.2 | APPROVED | |
| 15-20mm | ±0.3 | | |
| 20mm ABOVE | ±0.4 | UNIT: M/M | SCALE 7:1 |
| | | DATE | 2013.08.01 |

| PRODUCT NUMBER | VERSION |
|-------------------------------------|---------|
| XRF-2403M-TBGG/1/ | A00 |
| Xmultiple Technologies, Inc. | |
| ISO 9001-2008 | |

(RoHS Compliant)
Pb ≤ 4 wt%
Cd ≤ 75 ppm