

XRJF Series

RJ45, Shielded, Tab Down, w/o LED, w/Transformer

Part Numbering:

XRJF - XXX - X - X XX - X X X

NUMBER OF PORTS &
MECHANICAL TYPES
(SEE NOTE 1)

LED COLOR OPTIONS

PROTOCOL TYPES

- D: 10/100 Mbps, 4 cores or 6 cores
- E: 10/100 Mbps, 5 cores
- H: 10/100/1000 Mbps, 8 cores
- L: 10/100/1000 Mbps, 12 cores

CIRCUIT TYPES

LED POLARITY OPTIONS

- 0: Non-LED
- 1: + - , + -
- 2: + - , - +
- 3: - + , - +
- 4: Bi-color , Bi-color
- 5: Bi-color , + -
- 6: Bi-color , - +
- 7: + - , Bi-color
- 8: - + , Bi-color
- 9: Tri-color , Tri-color
- A: Tri-color , + -
- B: - + , + -

SPECIAL CODE OPTIONS

- 0: Standard
- 1: Operating Temperature -40°C ~ +85°C
- 2: Exterior base covered with PCB
- 3: Contact Gold plating 50u"
- 4: Housing material - Nylon
- 5: LED with resistance
- 6: HR1 R/R (contact pin right1 solder pin right 1)
- 7: R/L (contact pin right1 solder pin right 1)
- 8: Without Logo
- 9: Elecharacteristics follow Customer Request
- A: 8P10C→8P8C pin 1 & 10 eliminated
- B: With Logo, w/o part number and date code printed
- C: Remove partial pins
- D: LED with resistance; Housing material - Nylon
- F: LED - High Temp.
- G: Pantone 299 Blue
- H: LED use glue(KE45) to fix
- J: Without Logo, but with date code printed
- S: PBT+15U"(Small size for Samsung)
- Y: Pantone 114C Yellow


SHIELDING TYPES
(SEE NOTE 2)

RJ45, Shielded, Tab Down, w/o LED, w/Transformer **XRJF Series**

Note 1:

- 01A:** 1 port for XRJF or XRJG w/Horizontal LED pins(Modular)
- 01J:** 1 port for XRJF or XRJG w/Horizontal LED pins
- 02J:** 2 ports for XRJF or XRJG
- 04A:** 4 ports for XRJF or XRJG (Modular)
- 04J:** 4 ports for XRJF or XRJG

Note 2:



- 0:** Unshielded
- 1:** Y=3.05, EMI fingers on all sides
- 2:** Y=3.05, Non-EMI fingers
- 3:** Z=3.65, EMI fingers on all sides
- 4:** Z=3.65, Non-EMI fingers
- 5:** Z=3.05, EMI fingers on all sides
- 6:** Z=3.05, Non-EMI fingers
- 7:** EMI fingers on all sides
- 8:** Non-EMI fingers
- 9:** 4 Ports w/2 Tabs, Y=3.05, EMI fingers on all sides
- A:** 4 Ports w/3 Tabs, Y=3.05, EMI fingers on all sides
- B:** 4 Ports w/3 Tabs, Z=3.65, EMI fingers on all sides
- C:** 4 Ports w/3 Tabs, Z=3.65mm, Non-EMI fingers
- D:** 4 Ports w/o Tabs, Y=3.05, EMI fingers on all sides
- E:** 4 Ports w/3 Tabs, w/o Grounding, EMI finger on all sides
- G:** Y=3.05, EMI fingers on top side
- H:** EMI fingers on top side
- I:** 4 Ports w/3 Tabs, Y=3.05, EMI fingers on top side
- J:** 4 Ports w/o Tabs, Z=3.68, Non-EMI fingers
- K:** 4 Ports w/3 Tabs, Y=3.05, Non-EMI fingers
- L:** 4 Ports w/2 Tabs, Y=3.05, Non-EMI fingers
- M:** 4 Ports w/3 Tabs, Z=3.05, Non-EMI fingers
- N:** 4 Ports w/o Tabs, Y=3.05, Non-EMI fingers

