



RECOMMENDED MOUNTING HOLE  
 MAXIMUM PANEL THICKNESS: 5.5MM

NOTES:

1. MATERIALS:

- ① CENTER CONTACT: PHOSPHOR BRONZE, GOLD PLATING
- ② BODY: ZINC ALLOY, NICKEL PLATING
- ③ INSULATOR: PE-606
- ④ MOUNTING POST: BRASS, TIN PLATING
- ⑤ SOLDER TAIL: BRASS WIRE, TIN PLATING

2. UNSPECIFIED TOLERANCE: .XX ±0.25 [0.010]  
 .X ±0.30 [0.012]

RoHS Compliant

<b>X</b> MULTIPLE		THE INFORMATION AGE	
<small>XMULTIPLE ASIA          4F, No. 347, Yang Guang St.,          Neihu, Taipei, Taiwan 11475</small>		<small>XMULTIPLE USA          1420 Los Angeles Ave., Suite G,          Simi Valley, CA 93065</small>	
THIS DRAWING IS A CONTROLLED DOCUMENT.		G/NO:	
TITLE: 75 OHM BNC R/A PCB/PANEL MOUNT JACK, METAL BODY		DWG NO: XMRF-MCX-006	
PART NO: XMRF-MCX-006		DRAWN: LEON	
		CHKD: JEFF	
		DATE: Sep.20,07	
UNIT mm[inch]	SHEET 1 of 1	REV 02	