



X-Sealant GEL Specifications and Material Safety Data

Material Safety Data Sheet U.S. Department of Labor
May be used to comply with Occupational Safety and Health Administration
OSHA's Hazard Communication Standard (Non-Mandatory Form)
29 CFR 1910.1200. Standard must be consulted Form Approved
for specific requirements OMB No. 1218-0072

CORROSION AND CONNECTOR GEL be marked to indicate that.
Part Numbers- 82003, 82016

SECTION I

Xmultiple Technologies Inc.
Emergency Telephone Number: 805-579-1100
Address: 1420 Los Angeles Ave, Simi Valley, CA 93065
Date Prepared: January 2, 2008

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Other Limits

Hazardous Components OSHA PEL ACGIH TLV Recommended Percentages
(Specific Chemical/Identity; Common Name(s))

SYNTHETIC HYDROCARBONS CAS#68037-01-4 70-80%

HYDRO TREATED POLYMER CAS#8042-47-5 10-20%

FUMED SILICA CAS# 68611-44-9 7-10%

ANTI-OXIDANT CAS# 41484-35-9 1-2%

C11-14 BRANCHED ALYKLAMINES CAS# 80939-62-4 .5-1.5%

BARIUM PETROLEUM SULFONATE CAS# 61790-48-5 .1-.25%

THEMAL STABILIZER CAS#68648-89-5 3-5%

UNAMINE O CAS# 27136-73-8 .25-1%

POLYGLYCOL CAS# 025322-69-4 1-2%

ALL INGREDIENTS ARE TSCA LISTED

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point N/A Specific Gravity (H₂O = 1) .89

Vapor Pressure (mm Hg.) N/A Melting Point N/A

Vapor Density (AIR = 1) N/A Evaporation Rate (Butyl Acetate = 1) N/A

Solubility in Water: NOT SOLUBLE

Appearance and Odor: OLIVE GREEN COLOR, SLIGHT ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method used) N/A Flammable Limits LEL UEL

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Special Fire Fighting Procedures: WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL
CONTAINERS EXPOSED TO HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING

WATER OR FOAM AS FROTHING MAY OCCUR. Unusual Fire and Explosion Hazards: DENSE SMOKE MAY BE GENERATED WHILE BURNING CARBON MONOXIDE. CARBON DIOXIDE AND OTHER OXIDES MAY BE GENERATED AS PRODUCTS OF COMBUSTION.

SECTION V - REACTIVITY DATA

Stability: Unstable: Conditions to avoid:

Stable: YES Conditions to avoid: NONE KNOWN

Incompatibility (*materials to avoid*): MAY REACT WITH STRONG OXIDIZING AGENTS

Hazardous Decomposition or Byproducts

Hazardous Polymerization: May occur: Conditions to avoid:

Will not occur: YES Conditions to avoid: NONE KNOWN

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry: INHALATION? SKIN? INGESTION?

Health Hazards (*Acute and Chronic*): EYE: THIS PRODUCT IS MINIMALLY IRRITATING TO EYES UPON DIRECT CONTACT. SKIN: SLIGHT IRRITATION.

Carcinogenicity: NTP? NOT LISTED IARC MONOGRAPHS? NOT LISTED OSHA REGULATIONS? NOT LISTED Signs and Symptoms of Exposure: CONTACT WITH EYE MAY RESULT IN SLIGHT IRRITATION. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD IRRITATIONS.

Medical Conditions Generally Aggravated by Exposure: N/E Emergency and First Aid Procedures: SKIN: REMOVE BY WIPING AND WASH WITH SOAP AND WATER. EYES: WASH WITH COPIOUS AMOUNTS OF WATER. INHALATION: REMOVE TO OPEN AIR.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: SPILLS SHOULD BE ABSORBED OR SCRAPED UP.

Waste Disposal Method: USE METHOD OUTLINED IN LOCAL EPA AND GOVERNMENTAL REGULATIONS.

Precautions to be Taken in Handling and Storage: KEEP CONTAINERS CLOSED. GOOD MANUFACTURING PRACTICES SHOULD BE FOLLOWED IN HANDLING AND STORAGE.

Other Precautions: SURFACE SUBJECT TO SPILLS WITH THIS PRODUCT CAN BECOME SLIPPERY.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (*Specify Type*): NONE REQUIRED

Ventillation Local Exhaust N/A Special: N/A

Mechanical (*General*) N/A Other: N/A

Protective Gloves: YES Eye Protection: YES

Other Protective Clothing or Equipment: EYE BATH AND SAFETY SHOWER

Work Hygienic Practices: NORMAL PRECAUTIONS COMMON TO GOOD MANUFACTURING PRACTICES SHOULD BE FOLLOWED.